

ECOMBI



Technical features

- ▶ Silent performance.
- ▶ Temperature sensor with calibration option.
- ▶ Overheating protection at storage heating.
- ▶ Safety thermostat with manual reset.
- ▶ Predictive heating element made of Aluminium.
- ▶ Storage heating elements made of stainless steel.
- ▶ Microtherm G 12mm insulation, vermiculite and ecological fibre.
- ▶ Front, side and rear air isolating chambers.
- ▶ Storage core made of a specially designed material for ECOMBI.
- ▶ Steel structure powder coated in epoxy RAL 9010.
- ▶ Robust plastic fittings.
- ▶ Easy to install on any kind of wall.
- ▶ Very intuitive keyboard with lock option.
- ▶ Compatible with two-period off peak electric tariff in a single 24-hour interval.
- ▶ Daily and weekly programming.
- ▶ Deferred storage energy option.
- ▶ Storage, Combined storage, Convection, Frost protection and Automatic ECOMBI operation modes can be set up.
- ▶ Weekly programming.
- ▶ Visual alarm.



| MODEL | ECO158 | ECO208 | ECO308 | ECO408 |
|--------------------------------|---------------|----------------|-----------------|-----------------|
| Predictive emitter power* | 450W | 600W | 900W | 1200W |
| Storage power | 985W | 1310W | 1960W | 2620W |
| Charging (8h) | 7.9 kWh | 10.5 kWh | 15.7 kWh | 21.0 kWh |
| Connection | 240 V ~ 60Hz | 240 V ~ 60Hz | 240 V ~ 60Hz | 240 V ~ 60Hz |
| Length | 55cm (21.5") | 66cm (26") | 89cm (35") | 111cm (43.5") |
| Height | 73cm (28.5") | 73cm (28.5") | 73cm (28.5") | 73cm (28.5") |
| Depth | 18cm (7") | 18cm (7") | 18cm (7") | 18cm (7") |
| Weight | 57kg(126 lbs) | 76kg (168 lbs) | 111kg (245 lbs) | 147kg (324 lbs) |
| Insulation | Class I | Class I | Class I | Class I |
| Num. of bricks 7,5kg (16.5lbs) | - | 8 | 12 | 16 |
| Num. of bricks 11,3kg (25lbs) | 4 | - | - | - |
| Brick package ref. | 11072 | 11016 | 11016 | 11016 |

*Storage heater elements and predictive emitter element will never operate at the same time.